

Sr. No.	Industry	Parameter	Standards
1	2	3	4
	Note :	1. Water Consumption for the Jute processing industry will be 1.5 Cum/Ton of product from January, 1992.	
		2. At the present no limit for colour is given for liquid effluent. However, as far as possible colour should be removed.	
		* Stack emissions from boiler house shall conform to the standards already prescribed under Environment (Protection) Act, 1986, vide Notification No. GSR 742(E), dated 30.08.90.	
53.	LARGE PULP & PAPER NEWS PRINT/ RAYON GRADE PLANTS OF ¹[CAPACITY ABOVE 24000 MT PER ANNUM]	EFFLUENTS	Concentration in mg/l except pH and TOCL
		pH	7.0 – 8.5
		BOD ² [3 days at 27°C]	30
		COD	350
		Suspended Solids	500
		³ [Absorbable Organic Halogens (AOX) in effluent discharge	1.5 kg/ton of product with effect from the date of publication of this notification.1.0 kg/ton of product with effect from the 1 st day of March,2008.]
		Flow (Total Waste Water Discharge)	
		** (i) Large Pulp & Paper	200 Cum/Ton of Paper produced
		(ii) Large Rayon Grade Newsprint	150 Cum/Ton of Paper produced.
54.	SMALL PULP AND PAPER Paper Plant of Capacity upto 24000 MT/Annum :	EFFLUENT	
	Category :		
	A. *Agrobased	Total waste water discharge	200 cum/Ton of paper produced
	B. **Waste paper based	Total waste water discharge	75 cum/Ton of paper produced

¹ Substituted by Rule 2(ii) (a) of the Environment (Protection) Third Amendments Rules, 2005 notified vide Notification No.G.S.R.546(E), dated 30.8.2005.

² Substituted by Rule 2 of the Environment (Protection) Amendment Rules, 1996 notified by G.S.R.176(E), dated 2.4.1996 may be read as BOD (3 days at 27°C) wherever BOD 5 days 20°C occurred

³ Substituted by Rule 2(ii) (b) of the Environment (Protection) Third Amendments Rules, 2005 notified vide Notification No.G.S.R.546(E), dated 30.8.2005

** The Standards with respect of total wastewater discharge for the large pulp and paper mills be established from 1992, will meet the standards of 100 cum/Ton of paper produced.