

Sr. No.	Industry	Parameter	Standards
1	2	3	4
*60.	MAN-MADE FIBRE INDUSTRY (SEMI-SYNTHETIC)	EFFLUENTS	(Concentration in mg/l except for pH)
		pH	5.5 - 9.0
		Suspended Solids	100
		BOD ¹ [3 days at 27°C]	30
		Zinc (as Zn)	1
61	CERAMIC INDUSTRY	EMISSIONS	(Concentration in mg/Nm ³)
	A. Kilns		
	(a) Tunnel, Top Hat, Chamber	Particulate Matter	150
		Fluoride	10
		Chloride	100
		Sulphur dioxide	**
	(b) Down-draft	Particulate Matter	1200
		Fluoride	10
		Chloride	100
		Sulphur dioxide	**
	(c) Shuttle	Particulate Matter	150
		Fluoride	10
		Chloride	100
		Sulphur dioxide	**
	(d) Vertical Shaft Kiln	Particulate Matter	250
		Fluoride	10
		Sulphur dioxide	**
	(e) Tank furnace	Particulate Matter	150
		Fluoride	10
		Sulphur dioxide	**
	B. Raw material handling, Processing and operations		
	(a) Dry raw materials handling and processing operations	Particulate Matter	150
	(b) Basic raw material and processing operations	Particulate Matter	*
	(c) Other sources of air pollution Generation	Particulate Matter	*
	C. Automatic Spray Unit		
	(a) Dryers		
	(i) Fuel fired dryers	Particulate matter	150
	(ii) For heat recovery dryer	Particulate matter	*
	(b) Mechanical finishing operation	Particulate matter	*
	(c) Lime/Plasters of Paris manufacture		

* Standards notified at Sr. No.2 may also be referred.

¹ Substituted by Rule 2 of the Environment (Protection) Amendment Rules, 1996 notified by G.S.R.176(E), dated 2.4.1996 may be read as BOD (3 days at 27°C) wherever BOD 5 days 20°C occurred.