

S. No.	Industry	Parameter	Standards
1.	2.	3.	4.
¹ [62.	VISCOSE FILAMENT YARN (Sub-sector of manmade fibre semi- Synthetic Industry)	EFFLUENTS	(Concentration in mg/l except for pH)
		pH	5.5-9.0
		Suspended solids	100
		BOD(3 days at 27°C)	30
		Zinc (as Zn)	5
² [63.	STARCH INDUSTRY (Maize products)	EFFLUENTS:	Concentration not to exceed mg/l (except pH and waste water discharge)
		pH	6.5-8.5
		BOD (3 days at 27°C)	
		Suspended Solids	150
		Wastewater discharge	8 m ³ /tonne of maize Processed

Note : The prescribed limits for BOD and suspended solids shall be made more stringent or less stringent depending upon the conditions and local requirements as mentioned below :

- (i) BOD shall be made stringent upto 30mg/l if the recipient fresh water body is a source for drinking water supply.
- (ii) BOD shall be allowed upto 350 mg/l for applying on land provided the land is designed and operated as a secondary treatment system with the requisite monitoring facilities. The drainage water

¹ Sl. No. 62 and entries relating thereto inserted by Rule 2(b) of the Environment (Protection) Third Amendment Rules, 1993 by G.S.R. No. 801 (E), dated 31.12.1993.

² Sl.No.63 to 78 and entries relating thereto inserted by Rule 3 (a) of the Environment (Protection) (Amendment) Rules, 1996 notified by G.S.R.176(E), dated 2.4.1996.

* Substituted by Rule 2 of the Environment (Protection) Amendment Rules, 1996 notified by G.S.R.176(E), dated 2.4.1996 may be read as BOD (3 days at 27°C) wherever BOD 5 days 20°C occurred.