

- Water consumption in the coal washery shall not exceed 1.5 cubic meter per tonne of coal.
- The efficiency of the setting ponds of the waste water treatment system of the coal washery shall not be less than 90%.
- Green belt shall be developed along the road side, coal handling plants, residential complex, office building and all around the boundary line of the coal washery.
- Storage bunkers, hoppers, rubber decks in chutes and centrifugal chutes shall be provided with proper rubber linings.
- Vehicles movement in the coal washery area shall be regulated effectively to avoid traffic congestion. High pressure horn shall be prohibited. Smoke emission from heavy duty vehicle operating in the coal washeries should conform the standards prescribed under Motor Vehicle Rules, 1989.

#### **86. WATER QUALITY STANDARDS FOR COASTAL WATERS MARINE OUTFALLS**

In a coastal segment marine water is subjected to several types of uses. Depending of the types of uses and activities, water quality criteria have been specified to determine its suitability for a particular purpose. Among the various types of uses there is one use that demands highest level of water quality/purity and that is termed a “designated best use” in that stretch of the coastal segment. Based on this, primary water quality criteria have been specified for following five designated best uses :-

Class	Designated best use
SW-I(See Table 1.1.)	Salt pans, Shell fishing, Mariculture and Ecologically Sensitive Zone
SW-II (See Table 1.2)	Bathing, Contact Water Sports and Commercial fishing.
SW-III (See Table 1.3)	Industrial cooling, Recreation(non-contact) and Aesthetics
SW-IV (See Table 1.4)	Harbour
SW-V (See Table 1.5)	Navigation and Controlled Waste Disposal

The Standards alongwith rationale/remarks for various parameters for different designated best uses, given in Table 1.1 to 1.5

**TABLE 1.1**  
**PRIMARY WATER QUALITY CRITERIA FOR CLASS SW-1 WATERS**  
**(For Salt pans, Shell fishing, Mariculture and Ecologically Sensitive Zone)**

S. No.	Parameter	Standards	Rationale/Remarks
1.	2.	3.	4.
1.	pH range	6.5---8.5	General broad range, conducive for propagation of aquatic lives is given. Value largely dependant upon soil-water interaction.
2.	Dissolved Oxygen	5.0 mg/l or 60 per cent saturation value whichever is higher	Not less than 3.5 mg/l at any time of the year for protection of aquatic lives.
3.	Colour and Odour	No noticeable colour or offensive odour.	Specially caused by chemical compound like creosols, phenols, naphtha pyridine benzene, toluene etc. causing visible colouration of salt crystal and fainting fish flesh.
4.	Floating Matters	Nothing obnoxious or detrimental for use purpose	Surfactants should not exceed an upper limit of 1.0 mg/l and the concentration not to cause any visible foam.
5.	Suspended Solids	None from sewage or industrial waste origin	Settleable inert matters not in such concentration that would impair any usages specially assigned to this class.
6.	Oil and Grease (including Petroleum Products)	0.1 mg/l	Concentration should not exceed 0.1 mg/l as because it has effect on fish eggs and larvae.
<sup>1</sup> [7.	Heavy Metals : Mercury (as Hg) Lead (as Pb) Cadmium (as Cd)	0.001 mg/l 0.001 mg/l 0.01 mg/l]	Values depend on : (i) Concentration in salt, fish and shell fish. (ii) Average per capita consumption per day. (iii) Minimum ingestion rate that induces symptoms of resulting diseases.

**Note :** SW-1 is desirable to be safe and relatively free from hazardous chemicals like pesticides, heavy metals and radionuclide concentrations. Their combined (synergistic or antagonistic) effects on health and aquatic lives are not yet clearly known. These chemicals undergo bio-accumulation, magnification and transfer to human and other animals through food chain. In areas where fisheries, salt pans are the governing considerations, and presence of such chemicals apprehended/reported, bioassay test should be performed following appropriate methods for the purpose of setting case specific limits.

<sup>1</sup> Substituted by Rule 2(iii) of the Environment (Protection) (Second Amendment) Rules, 1999 published in the Notification G.S.R.682(E), dated 5.10.1999.

TABLE 1.2

## PRIMARY WATER QUALITY CRITERIA FOR CLASS SW-II WATERS

(For Bathing, Contact Water Sports and Commercial Fishing)

S.No.	Parameter	Standards	Rationale/Remarks
1.	2.	3.	4.
1.	pH range	6.5---8.5	Range does not cause skin or eye irritation and is also conducive for propagation of aquatic lives.
2.	Dissolved Oxygen	4.0 mg/l or 50 per cent saturation value whichever is higher.	Not less than 3.5 mg/l at anytime for protection of aquatic lives.
3.	Colour and Odour	No noticeable colour or offensive odour	Specially caused by chemical compound like creosols phenols, naphtha, benzene, pyridine toluene etc. causing visible colouration of water and tainting of and odour in fish flesh.
4.	Floating Matters	Nothing obnoxious or detrimental for use purposes.	None in such concentration that would impair usages specially assigned to this class.
5.	Turbidity	30 NTU (Nephelo Turbidity Unit)	Measured at 0.9 depth
6.	Fecal Coliform	100/100 ml(MPN)	The average value not exceeding 200/100 ml in 20 per cent of samples in the year and in 3 consecutive samples in monsoon months.
7.	Biochemical Oxygen Demand (BOD) (3 days at 27°C)	3 mg/l	Restricted for bathing (aesthetic quality of water). Also prescribed by IS : 2296-1974.

**TABLE 1.3**  
**PRIMARY WATER QUALITY CRITERIA FOR CLASS SW-III WATERS**  
**[For Industrial Cooling, Recreation (non-contact) and Aesthetics]**

S.No.	Parameter	Standards	Rationale/Remarks
1.	2.	3.	4.
1.	pH range	6.5---8.5	The range is conducive for propagation of aquatic species and restoring natural system.
2.	Dissolved Oxygen	3.0 mg/l or 40 per cent saturation value whichever is higher.	To protect aquatic lives.
3.	Colour and Odour	No noticeable colour or offensive odour	None in such concentration that would impair usages specifically assigned to this class.
4.	Floating Matters	No visible, obnoxious floating debris, oil slick, scum.	As in (3) above.
5.	Fecal Coliform	500/100 ml(MPN)	Not exceeding 1000/100 ml in 20 percent of samples in the year and in 3 consecutive samples in monsoon months.
6.	Turbidity	30 NTU	Reasonably clear water for Recreation Aesthetic appreciation and Industrial cooling purposes.
*7.	Dissolved Iron (as Fe)	0.5 mg/l or less	It is desirable to have the collective concentration dissolved Fe and Mn less or equal to 0.5 mg/l to avoid scaling effect.
*8.	Dissolved Manganese (as Mn)	0.5 mg/l or less	

\* Standards included exclusively for Industrial Cooling purpose. Other parameters same.

TABLE 1.4

## PRIMARY WATER QUALITY CRITERIA FOR CLASS SW-IV WATERS

( For Harbour Waters)

S.No.	Parameter	Standards	Rationale/Remarks
1.	2.	3.	4.
1.	pH range	6.0---9.0	To minimize corrosive and scaling effect.
2.	Dissolved Oxygen	3.0 mg/l or 40 per cent saturation value whichever is higher.	Considering bio-degradation of oil and inhibition to oxygen production thorough photosynthesis.
3.	Colour and Odour	No visible colour or offensive odour	None from reactive chemicals which may corrode paints/ metallic surfaces.
4.	Floating materials, Oil, grease and scum (including Petroleum products)	10 mg/l	Floating matter should be free from excessive living organisms which may clog or coat operative parts of marine vessels/equipment.
5.	Fecal Coliform	500/100 ml(MPN)	Not exceeding 1000/100 ml in 20 per cent of samples in the year and in 3 consecutive samples in monsoon months.
6.	Biochemical Oxygen Demand (3 days at 27°C)	5mg/l	To maintain water relatively free from pollution caused by sewage and other decomposable wastes.

**TABLE 1.5**  
**PRIMARY WATER QUALITY CRITERIA FOR CLASS SW-V WATERS**  
**(For Navigation and Controlled Waste Disposal)**

S.No.	Parameter	Standards	Rationale/Remarks
1.	2.	3.	4.
1.	pH range	6.0---9.0	As specified by New England Interstate Water Pollution Control Commission.
2.	Dissolved Oxygen	3.0 mg/l or 40 per cent saturation value whichever is higher.	To protect aquatic lives.
3.	Colour and Odour	None in such concentrations that would impair any usages specifically assigned to this class.	As in (i) above.
4.	Sludge deposits, Solid refuse floating solids, oil grease and scum.	None except for such small amount that may result from discharge of appropriately treated sewage and or industrial waste effluents.	As in (i) above.
5.	Fecal Coliform	500/100 ml (MPN)	Not exceeding 1000/100 ml in 20 per cent of samples in the year and in 3 consecutive samples in monsoon months.