

Sr. No.	Industry	Parameter	Standards
1	2	3	4
# ¹ 11.	STONE CRUSHING UNIT	Suspended Particulate Matter	The suspended particulate matter measured between 3 metres and 10 metres from any process equipment of a stone crushing unit shall not exceed 600 microgrammes per cubic metre.
² 12.	COKE OVENS		Concentration in the effluents when discharged into inland surface waters not be exceed milligramme per litre (except for pH)
		pH	5.5 – 9.0
		Biochemical Oxygen Demand (27°C for 3 days)	30
		Suspended Solids	100
		Phenolic Compounds (as C ₆ H ₅ OH)	5
		Cynides (as CN)	0.2
		Oil & Grease	10
		Ammonical Nitrogen (as N)	50
13.	SYNTHETIC RUBBER		Concentration in the effluents when discharged into inland surface waters not be exceed milligramme per litre (except for colour and pH)
		Colour	Absent
		pH	5.5 – 9.0
		Biochemical Oxygen Demand ¹ [BOD (3 days at 27°C)]	50
		Chemical Oxygen Demand	250
		Oil and grease	10.0

¹ S.No.11 and entries relating thereto inserted vide SO 443(E)dt.18.4.87 published in the Gazette no. 206 dt. 18.4.87.
Standards notified at Sl. No. 37 may also be referred.

² S.Nos. 12 to 24 and entries relating thereto inserted vide S.O. 64(E) published in the Gazette No. 42 dt. 18.1.88.