

Sr. No.	Industry	Parameter	Standards
1	2	3	4
14.	SMALL PULP AND PAPER INDUSTRY		Concentration not be exceed mg/l (except for pH and sodium absorption ratio)
	*Discharge into inland surface water	pH	5.5 – 9.0
		Suspended Solids	100
		BOD	30
	Disposal on land	pH	5.5 – 9.0
		Suspended Solids	100
		BOD	100
		Sodium Absorption Ratio	26
		¹ [Absorbable Organic Halogens (AOX) in effluent discharge	3.00 kg/ton of paper produced with effect from the date of publication of this notification. 2.00 kg/ton of paper produced with effect from the 1 st day of March, 2006.

Explanation.- These standards shall apply to all small scale Pulp and Paper Mills having capacity below 24,000 MT per annum]

² 15.	FERMENTATION INDUSTRY (DISTILLERIES, MALTRIES AND BREWERIES)		Concentration in the effluents not to exceed milligramme per litre (except for pH and colour & odour)
		pH	5.5 – 9.0
		Colour & Odour	All efforts should be made to remove colour and unpleasant odour as far as practicable.
		Suspended Solids	100
		³ [BOD (3 days at 27°C)]	
		⁴ [-disposal into inland surface waters or river/ streams]	30
		- disposal on land or for irrigation]	100
		**[(2)...(7)]	

¹ Inserted by Rule 2 (i) of the Environment (Protection) Third Amendments Rules, 2005 notified vide Notification G.S.R.546(E), dated 30.8.2005.

² Entries relating to S.No. 15 corrected in terms of SO 12(E), dt. 8.1.90 published in the Gazette no. 10 dt. 8.1.90.

³ Substituted by Rule 2 of the Environment (Protection) Amendment Rules, 1996 notified by G.S.R.176(E), dated 2.4.1996 may be read as BOD (3 days at 27°C) wherever BOD 5 days 20°C occurred.

⁴ Substituted vide Rule 3(a) of the Environment (Protection) (Amendments) Rules, 1996 notified vide G.S.R.186(E), dated 2.4.1996