

Sr. No.	Industry	Parameter	Standards			
1	2	3	4			
	<b>Note :</b>	<sup>1</sup> [(1)] *Wastewater generation shall not exceed 250 metre cube per tonne of paper produced. <sup>2</sup> [(2).....(7)]				
16.	<b>LEATHER TANNERIES</b>		Concentration in the effluent not to exceed milligramme per litre (except for pH and per cent sodium)			
			Inland Surface Waters	Public Sewers	Land for Irrigation	Marine Coastal areas
			(a)	(b)	(c)	(d)
	Suspended Solids		100	00	200	100
	<sup>3</sup> [BOD 3 days at 27°C]		30	350	100	100
	pH		6.0 – 9.0	6.0 – 9.0	6.0 – 9.0	6.0 – 9.0
	Chlorides (as Cl)		1000	1000	200	-
	Hexavalent Chromium (Cr+6)		0.1	0.2	0.1	1.0
	Total Chromium (as Cr)		2.0	2.0	2.0	2.0
	Sulphides (as S)		2.0	5.0	-	5.0
	Sodium percent		-	60	60	-
	Boron (as B)		2.0	2.0	2.0	-
	Oil & Grease		10	20	10	20

<sup>1</sup> Renumbered as (1) by Notification No.S.O.12(E), dated 8.1.1990

<sup>2</sup> Notes 2 to 7 inserted by Notification S.O.12(E), dated 8.1.1990 and omitted by G.S.R.176(E), dated 2.4.1996 w.e.f. 3.4.1996

<sup>3</sup> Substituted by Rule 2 of the Environment (Protection) Amendment Rules, 1996 notified by G.S.R.176(E), dated 2.4.1996 may be read as BOD (3 days at 27°C) wherever BOD 5 days 20°C occurred.