

Sr. No.	Industry	Parameter	Standards
1	2	3	4
¹ [² 27.	ASBESTOS MANUFACTURING UNITS (INCLUDING ALL PROCESSES INVOLVING THE USE OF ASBESTOS)	- Pure Asbestos material	0.5 fibre */cc for one year from the date of notification 0.2 fibre */cc after one year from the date of notification]
		- Total Dust	2 mg/m ³ (normal)
28.	CALOR ALKALI (CAUSTIC SODA)	EMISSIONS	Concentration in mg/m ³ (normal)
	(a) Mercury Cell	Mercury (from hydrogen gas holder stack)	0.2
	(b) All processes	Chlorine (from hypo tower)	15.0
	(c) All processes	Hydro chloric acid vapours and mist (from hydro chloric acid plant)	35.0
29.	LARGE PULP AND PAPER	EMISSIONS	Concentration in mg/m ³ (normal)
		Particulate matter	250**
		H ₂ S	10
30.	INTEGRATED IRON AND STEEL PLANTS:	I. EMISSIONS	
	(a) Coke Oven	Particulate mater	50
	(b) Refractory material plant	Particulate matter	150
		II. EFFLUENTS	Concentration in mg/l except for pH.
	(a) Coke oven		
	By product plant.	pH	6.0 – 8.0
		Suspended Solids	100

¹ Standards mentioned at Sl. No.27 amended by Rule 2(III) of the Environment (Protection) First Amendment Rules, 2006 notified vide Notification G.S.R.46(E), dated 3.2.2006.

² S.No. 27 to 31 and entries relating thereto inserted vide GSR 913(E) dt. 24.10.89 published in the Gazette No. 554 dt. 24.10.89.

** This standard of 250 mg/m³ (normal) shall apply only for a period of 3 years with effect from the date on which the Environment (protection) Second Amendment Rules, 1989 came into force. After three years the standard to be applicable is 15 mg/m³ (normal).