

Sr. No.	Industry	Parameter	Standards
1	2	3	4
		Phenol	1.0
		Cynide	0.2
		BOD ¹ [(3 days at 27°C)]	30
		COD	250
		Ammonical Nitrogen	50
		Oil and Grease	10
	(b)Other plants such as sintering plant, blast furnace, steel melting and rolling mill:	pH	6.0 – 9.0
		Suspended Solids	100
		Oil and Grease	10
31.	RE-HEATING (REVERBERATORY) FURNACES: Capacity : All sizes	EMISSIONS	Concentration in mg/m ³ (normal)
	Sensitive area	Particulate matter	150
	Other area	Particulate matter	450
² [32.	FOUNDRIES	EMISSIONS	
	(a) Cupola Capacity (Melting Rate) :		
	Less than 3 mt./hr.	Particulate Matter	450
	3 mt/hr. and above	Particulate Matter	150
	Note : It is essential that stack is constructed over the cupola beyond the charging door and emissions are directed through the stack which should be at least six times the diameter of cupola.		
	(b) Arc Furnaces :		
	Capacity: All sizes	Particulate Matter	150

¹ Substituted by Rule 2 of the Environment (Protection) Amendment Rules, 1996 notified by G.S.R.176(E), dated 2.4.1996 may be read as BOD (3 days at 27°C) wherever BOD 5 days 20°C occurred

² S.No. 32 to 47 and entries relating thereon inserted vide GSR 742(E) dt. 30.8.90 published in the Gazette No. 365 dated 30.8.90.