

Sr. No.	Industry	Parameter	Standards
1	2	3	4
	Glass Industries (for all categories)	EFFLUENTS:	
		pH	6.5 – 8.5
		Total Suspended Solids	100 mg/l
		Oil & Grease	10 mg/l
49.	LIME KILN	Stack Height	
	Capacity :		
	Upto 5 T/day	Stack Height	A hood should be provided with a stack of 30 meter height from ground level (including kiln height).
	Above 5T/day	Stack height	$H=14(Q)^{0.3}$ where Q is emission rate of SO ₂ in kg/hr and H=Stack Height in meters.
	More than 5T/day and up to 40 T/Day	Particulate matter	500 mg/Nm ³
	Above 40T/day	Particulate matter	150 mg/Nm ³
50.	*SLAUGHTER HOUSE, MEAT & SEA FOOD INDUSTRY	EFFLUENTS	Concentration in mg/l
	Category		
	A.Slaughter House		
	(a) Above 70 TLWK/day	BOD ¹ [3 days at 27°C]	100
		Suspended Solids	100
		Oil and Grease	10
	(b) 70 TLWK/day below	BOD ¹ [3 days at 27°C]	500
	B.Meat Processing		
	(a) Frozen Meat	BOD ¹ [3 days at 27°C]	30
		Suspended Solids	50
		Oil & Grease	10
	(b) Raw Meat from own Slaughter House.	BOD ¹ [3 days at 27°C]	30
		Suspended Solids	50
		Oil & Grease	10
	(c) Raw Meat from other sources		Disposal via Screen and Septic Tank.
	C.Sea Food Industry	BOD ¹ [3 days at 27°C]	30
		Suspended Solids	50
		Oil and Grease	10

* The emission standards from Boiler House shall conform to the standards already prescribed under E(P) Act, 1986 vide notification No.G.S.R.742(E), dated 30.8.90.

¹ Substituted by Rule 2 of the Environment (Protection) Amendment Rules, 1996 notified by G.S.R.176(E), dated 2.4.1996 may be read as BOD (3 days at 27°C) wherever BOD 5 days 20°C occurred.