

¹[83. **STANDARDS/GUIDELINES FOR CONTROL OF NOISE POLLUTION FROM STATIONARY DIESEL GENERATOR(DG) SETS**

* * *]

84. TEMPERATURE LIMIT FOR DISCHARGE OF CONDENSER COOLING WATER FROM THERMAL POWER PLANT

A . New thermal power plants commissioned after June 1,1999.

New thermal power plants, which will be using water from rivers/lakes./ reservoirs shall install cooling towers-irrespective location and capacity. Thermal power plants which will use sea water for cooling purposes, the condition below will apply.

B. New projects in coastal areas using sea water.

The thermal power plants using sea water should adopt suitable system to reduce water temperature at the final discharge point so that the resultant rise in the temperature of receiving water does not exceed 7°C over and above the ambient temperature of the receiving water bodies.

C. Existing thermal power plants.

Rise in temperature of condenser cooling water from inlet to the outlet of condenser shall not be more than 10°C.

D. Guidelines for discharge point :

1. The discharge point shall preferably be located at the bottom of the water body at mid-stream for proper dispersion of thermal discharge.
2. In case of discharge of cooling water into sea, proper marine outfall shall be designed to achieve the prescribed standards. The point of discharge may be selected in consultation with concerned State Authorities/NOI.
3. No cooling water discharge shall be permitted in estuaries or near ecologically sensitive areas such as mangroves, coral reefs/spawning and breeding grounds of aquatic flora and fauna.

85. ENVIRONMENTAL STANDARDS FOR COAL WASHERIES

1. Fugitive emission standards.
 - The difference in the value of suspended particulate matter, delta (Δ), measured between 25 and 30 metre from the enclosure of coal crushing plant in the downward and leeward wind direction shall not exceed 150 microgram per cubic meter. Method of measurement shall be High Volume Sampling and Average flow rate, not less than 1.1 m³ per minute, using upwind downwind method of measurement :

¹ Serial No..83 and entries relating thereto omitted by Rule 2 (b) of the Environment (Protection) Second Amendment Rules, 2002 notified vide notification G.S.R. 371(E), dated 17.5.2002.

2. Effluent discharge standards

- The coal washeries shall maintain the close circuit operation with zero effluent discharge.
- If in case due to some genuine problems like periodic cleaning of the system, heavy rainfall etc. it become necessary to discharge the effluent to sewer land stream then the effluent shall conform to the following standards at the final outlet of the coal washery.

S.No.	Parameter	Limits
1.	pH	5.5—9.0
2.	Total suspended solids	100 mg/l
3.	Oil & Grease	10 mg/l
4.	B.O.D (3 days 27°C)	30 mg/l
5.	COD	250 mg/l
6.	Phenolics	1.0 mg/l

3. Noise level standards

- Operational/Working zone—not to exceed 85 dB(A) Leq for 8 hours exposure.
- The ambient air quality standards in respect of noise as notified under Environmental (Protection)Rules,1986 shall be followed at the boundary line of the coal washery.

4. Code of practice for Coal Washery.

- Water or Water mixed chemical shall be sprayed at all strategic coal transfer points such as conveyors, loading/unloading points etc. As far as practically possible conveyors, transfer points etc. shall be provided with enclosures.
- The crushers/pulverisers of the coal washeries shall be provided with enclosures, fitted with suitable air pollution control measures and finally emitted through a stack of minimum height of 30m. conforming particulate matter emission standard of 150 mg/Nm³ or provided with adequate water sprinkling arrangement.
- Water sprinkling by using fine atomizer nozzles arrangement shall be provided on the coal heaps and on around the crushers/pulverisers.
- Area, in and around the coal washery shall be pucca either asphalted or concreted.

- Water consumption in the coal washery shall not exceed 1.5 cubic meter per tonne of coal.
- The efficiency of the setting ponds of the waste water treatment system of the coal washery shall not be less than 90%.
- Green belt shall be developed along the road side, coal handling plants, residential complex, office building and all around the boundary line of the coal washery.
- Storage bunkers, hoppers, rubber decks in chutes and centrifugal chutes shall be provided with proper rubber linings.
- Vehicles movement in the coal washery area shall be regulated effectively to avoid traffic congestion. High pressure horn shall be prohibited. Smoke emission from heavy duty vehicle operating in the coal washeries should conform the standards prescribed under Motor Vehicle Rules, 1989.

86. WATER QUALITY STANDARDS FOR COASTAL WATERS MARINE OUTFALLS

In a coastal segment marine water is subjected to several types of uses. Depending of the types of uses and activities, water quality criteria have been specified to determine its suitability for a particular purpose. Among the various types of uses there is one use that demands highest level of water quality/purity and that is termed a “designated best use” in that stretch of the coastal segment. Based on this, primary water quality criteria have been specified for following five designated best uses :-

Class	Designated best use
SW-1(See Table 1.1.)	Salt pans, Shell fishing, Mariculture and Ecologically Sensitive Zone
SW-II (See Table 1.2)	Bathing, Contact Water Sports and Commercial fishing.
SW-III (See Table 1.3)	Industrial cooling, Recreation(non-contact) and Aesthetics
SW-IV (See Table 1.4)	Harbour
SW-V (See Table 1.5)	Navigation and Controlled Waste Disposal

The Standards alongwith rationale/remarks for various parameters for different designated best uses, given in Table 1.1 to 1.5