

To,

As per list enclosed

Sir,

Sealed quotations are invited on the behalf of Central Pollution Control Board from the experienced and eligible contractors/firms for the following works: **Renovation of MS Chamber-Civil & electrical works at 2nd floor** of Parivesh Bhawen. The scope of work is as below: -

Scope of work: -

S.N	Description of work	Unit	Qty	Rate (Rs.)	Amount (Rs.)
1.	Disposal of moorum/building rubbish/ malba/ similar unserviceable, dismantled or waste material by mechanical transport including loading, transporting, unloading to approved municipal dumping ground for lead upto 10 km for all lifts, complete as per directions of Engineer-in-charge	cum	10		
2.	Dismantling aluminium/ Gypsum partitions, doors, windows, fixed glazing and false ceiling including disposal of unserviceable material and stacking of serviceable material with in 50 meters lead as directed by Engineer-in-charge	sqm	150		
3.	12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)	sqm	20		
4.	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete	sqm	90		
5.	Applying priming coats with primer of approved brand and manufacture, having low VOC (Volatile Organic Compound) content. With water thinnable cement primer on wall surface having VOC content less than 50 grams/litre	sqm	90		
6.	Providing and fixing mineral fibre false ceiling tiles at all heights of size 595X595mm of approved texture, design and pattern. The tiles should have Humidity Resistance (RH) of 99%, Light Reflectance 85%, Thermal Conductivity k = 0.052 - 0.057 w/m K, Fire Performance as per (BS 476 pt - 6 &7)in true horizontal level suspended on interlocking T-Grid of hot dipped all round galvanized iron section of 0.33 mm thick (galvanized @120 gsm) comprising of main T runners of 15x32 mm of length 3000 mm, cross T of size 15x32mm of length 1200 mm and secondary intermediate cross T of size 15x32 mm of length 600 mm to form grid module of size 600x600 mm suspended from ceiling using galvanized mild steel item (galvanised@80gsm) 50 mm long 8mm outer diameter M-6 dash fasteners, 6 mm diameter fully threaded hanger rod up to 1000 mm length and L-shape level adjuster of size 85x25x2 mm, spaced at 1200 mm centre to centre along main 'T'. The system should rest on periphery walls /partitions with the help of GI perimeter wall angle of size24x24X3000 mm made of 0.40 mm thick sheet, to be	sqm	45		

	<p>fixed to the wall with help of plastic rawl plug at 450 mm centre to centre & 40 mm long dry wall S.S. screws. The exposed bottom portion of all T-sections used in false ceiling support system shall be pre-painted with polyester baked paint, for all heights. The work shall be carried out as per specifications, drawings and as per directions of the engineer-in-charge.</p> <p>With 16 mm thick beveled tegular mineral fibre Antimicrobial false ceiling tile confirming to ISO 5 (class 100) specifications</p>				
7.	Wall painting with premium acrylic emulsion paint of interior grade, having VOC (Volatile Organic Compound) content less than 50 grams/ litre of approved brand and manufacture, including applying additional coats wherever required to achieve even shade and colour. - Two coats	sqm	90		
8.	SITC of 36 watt energy efficiency recessed mounted LED luminaries suitable for 2 x 2 grid ceiling of one colors white in combination with profiled and flat diffuser : Lumen Output of 3300 lumens available in 4000 K & 5000 K color temperature constraint current electronic driver complete with all accessories i/c connection with 1.5 sq. mm PVC copper conductor single core cable & earthing etc. as reqd. (Bajaj make model no BCTBLR 39WATN NW / Wipro/Crompton /GE/ Philips/ Twinkle)	Nos	8		
9.	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required. Group C	Point	8		
10.	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed steel conduit as required. 2 X 4 sq. mm + 1 X 4 sq. mm earth wire	Meter	100		
11.	Supplying & fixing suitable size GI box with modular plate and cover in front on surface or in recess including providing and fixing 25 A modular socket outlet and 25 A modular SP MCB, "C" curve including connections, painting etc. as required.	Each	6		
12.	Supplying and fixing following size/ modules, GI box alongwith modular base & cover plate for modular switches in recess etc. as required. 8 Module (125mmX125mm)	Each	6		
13.	Supplying and fixing following modular switch/ socket on the existing modular plate & switch box including connections but excluding modular plate etc. as required.				
i.	15/16 A switch	Each	18		
ii.	6 pin 15/16 A socket outlet	Each	12		
14.	SITC of wall mounted cabin fan of 400 mm sweep i/c testing and commissioning etc. as reqd. (Bajaj/Khaitan/crompton/usha/ make)	Each	1		
15.	Supplying and fixing following modular switch/ socket on the existing modular plate & switch box including connections but excluding modular plate etc. as required. Telephone socket outlet	Each	4		

16.	Supplying and drawing of UTP 4 pair CAT 6 LAN Cable in the existing surface/ recessed Steel/ PVC conduit as required. 1 run of cable	Metre	200		
	Total				
	GST				
	Grand total				

Terms & Conditions: -

1. Sealed quotations should be submitted in the tender box kept at reception (Ground floor) of Parivesh Bhawan, CPCB on or before 25.05.2022 by 11.00 a.m.
2. The bidders have to submit valid copy of PAN Card, GST registration and copy of list of empanelment in CPWD or any other Govt. Organization and EMD of Rs. 4800/- as DD/FDR in favour of Central Pollution Control Board alongwith the bid, failing which the bid will be rejected.
3. **The work should be completed within 15 days from the issue of work order.**
4. Income Tax shall be deducted at source.
5. It may be noted that mere quoting the lowest rates will not entitle any firm to get the work order.
6. The Chairman, Central Pollution Control Board reserves the right to cancel any or all the quotations without assigning any reasons thereof.
7. The quotations shall be valid for 30 days from the date of their opening.
8. The payment will be released after completion of work.
9. The work shall be carried out strictly according to CPWD specifications for civil works.
10. The GST Registration no. of Central Pollution Control Board is 07AAALC0228L2ZD.
11. The terms & conditions and taxes etc. should be clearly mentioned in the quotation.
12. The over writing and corrections, if any should be counter signed.
13. Please note that CPCB Central Laboratory is maintaining OH&SMS (IS 18001:2007/2012), the personal deputed for work shall abide the required guidelines of safety while working in CPCB.
14. In the event of any dispute, the decision of the Chairman, Central Board shall be final and binding on both the parties.
15. Typographical & clerical errors are subject to correction.

Yours faithfully,

(Dinabandhu Gouda)
Divisional Head, Building

Copy to: I/c, F&A, CPCB